

We have the sensors adapted to your uses



SMART METERING



SMART BUILDING



SMART CITY



SMART INDUSTRY
















SMART FARMING

nke WATTECO is one of the European leaders in the design and manufacturing of smart sensors and multiprotocol remote data collection (GSM, LoRaWAN™, SigFox, Wireless MBus, LTE M...) solutions.

Our leadership is backed by over 30 years of experience in the design, development, industrialisation and manufacturing of electronic instruments as thermostat and automat for harsh or highly secure environments.



LoRaWAN™ SENSORS RANGE

FUNCTIONS	VISUAL	DESIGNATION	CLASS	POWER SUPPLY & AUTONOMY - SF12	REFERENCE
		HARVESTING THR SENSOR Indoor temperature, relative humidity, luminosity measurement.	A	3,6V - 1,1Ah lithium battery, solar cell Autonomy: 3 years without light 1 measure/10 mn & 1 report/30 mn	50-70-007
		INDOOR THR SENSOR Indoor temperature and relative humidity measurement.	A	3,6V - 3600mAh lithium battery Autonomy: 9 years - 1 measure/10mn & 1 report/h (data compressed)	50-70-053
		INDOOR TEMPERATURE SENSOR Indoor temperature measurement.	A	3,6V - 3600mAh lithium battery Autonomy: 9 years - 1 measure/10mn & 1 report/h (data compressed)	50-70-085
		REMOTE TEMPERATURE SENSOR Temperature measurement to supervise hot spots, cold chain & buildings. Collection: <ul style="list-style-type: none"> with 1 probe with 2 probes 	A	3,6V - 3600mAh lithium battery Autonomy: >10 years - 1 measure/h & 1 report/day (data compressed)	50-70-043 50-70-139
		CELS'O SENSOR Cold temperature measurement locally store 30 days of data on the basis of 1 measure / h.	A	3,6V - 3600mAh lithium battery Autonomy: > 7 years - 4 measures/h & 1 report/h (data compressed)	50-70-049
		ATM'O SENSOR Outdoor Temperature, relative humidity & atmospheric pressure measurement.	A	3,6V - 7200mAh lithium battery Autonomy: >5 years - 1 measure & 1 report/10mn; >8 years - 2 measures & 1 report/h	50-70-099
		PULSE S0 SENSOR ATEX Counting pulses generated by a water/gas meter any pulse meter in technical indoor column.	A	3,6V / 1200mAh lithium battery AtEx Zone II compliant Autonomy: > 3 years for 1 measure/h & 1 report/day	50-70-001
		PULSE SENS'O SENSOR Up/Down pulse counting for water/gaz/ electric/ energy meters. Capability to monitor up to 3 meters simultaneously. Collection: <ul style="list-style-type: none"> Remote Outdoor Pulse SENS'O Remote Outdoor Pulse SENS'O AtEx Waterproof remote Pulse SENS'O Waterproof remote Pulse SENS'O AtEx 	A	3,6V / 3600mAh lithium battery Autonomy: >10 years: 1 measure/h & 1 report/day	50-70-014 50-70-072 50-70-039 50-70-051
		IN'O SENSOR Transforming any type of binary I/O sensor into a remote wireless sensor report from 10 inputs & 4 outputs.	A C	3,6V / 3600mAh lithium battery 9V-24V / 300mW external power supply Autonomy: No limit or 10 years for 1 measure/h and 1 report/day	50-70-016 50-70-087
		PRESS'O SENSOR Two analog input transforming any gauge type of 0-10V, 4-20mA analog sensor into a remote wireless sensor.	A	3,6V / 3600mAh lithium battery 9V-24V / 300mW external power supply; Autonomy: 5 years for 24 measurements & 1 report/day	50-70-017
		MODBUS RS485 SENSOR Data collection from any ModBus RTU slave equipment.	A C	3,6V / 3600mAh -lithium battery or 9V-24V 100mW - external supply Autonomy: No limit or >10 years - 4 bytes every 30mn in SF12	50-70-080 50-70-109
		TIC SENSOR Remote reading of electronic & electricity meters from ENEDIS network, via the TIC output. Collection: <ul style="list-style-type: none"> TIC TIC Harvesting TIC +2S0; TIC +2S0 +2 Tores PME PMI 	A C	Harvesting - External 230 VAC - External 3,6V-24 VDC or 6V-18Ah battery; I1-A (Linky) Autonomy: no limit	50-70-008 50-70-002 50-70-038 50-70-045
		LEV'O SENSOR Measurement of the absolute pressure of liquid (water, oil, etc.).	A	3,6V - 7200mAh lithium battery Autonomy: >10 years - 1 measure/day & report/day	50-70-089

LoRaWAN™ SENSORS RANGE

FUNCTIONS	VISUAL	DESIGNATION	CLASS	POWER SUPPLY & AUTONOMY - SF12	REFERENCE
		FLASH'O SENSOR Transmitting the accumulated flash LED numbers from any pulse meters: water/ gas/electricity/energy.	A	3.6V - 3600mAh lithium battery Autonomy: >10 years - 1 measure & report/day; >8 years - 1 measure/h & 1 report/day	50-70-071
		INTENS'O SENSOR Measures the intensity of electrical power and determines the state of the equipment.	A	3,6V / 3600mAh -lithium battery Autonomy: 10 years - 1 measure/mn & 1 report/h; 7 years - 1 measure/2 sec. & 1 report/4h	50-70-098
		SMART PLUG Measure & report the energy, control the connected load, measure the quality of electrical network.	C	230VAC. +10%/-15% ; 50Hz Autonomy: no limit	50-70-003
		SMART PILOT WIRE capability to control electric heater ; relay control; actuator status report.	C	230VAC. +10%/-15% ; 50Hz Autonomy: no limit	50-70-027
		TRIPHAS'O SENSOR Measurement for active & reactive energy and power with rogowski coil and split core current transformer: <ul style="list-style-type: none"> ▪ with Tores 60 A ▪ with Tores 300 A ▪ without Tores Rogowski coil 4 000A ▪ with Tores Rogowski coil 4 000A. 	C	230VAC. - 400VAC +10%/-15% Autonomy: no limit	50-70-105 50-70-145 50-70-146 50-70-147
		VENTIL'O SENSOR Measure and transmit over long distance air depression in the centralized ventilation chambers, sanitary, gas.	A	3,6V / 3600mAh lithium battery Autonomy: >10 years: Pressure only - 1 measure/h & 1 report/day > 10 years: 1 measure/15 mn & 1 report/6h	50-70-101
		CLOS'O SENSOR Help to determine if a door is properly closed; tamper detection.	A	3,6V / 3600mAh lithium battery Autonomy: > 7 years with 1 report/day	50-70-108
		MAGNET'O SENSOR Door opening detection (Indoor).	A	3,6V / 1200mAh lithium battery Autonomy: > 3 years for 1 transmission/day	50-70-134
		SKYDOME SENSOR Verifies that a roof window is properly closed and detects a change of position thanks to an onboard inclinometer.	A	3,6V - 3600mAh lithium battery Autonomy: > 8 years - 1 measure / 10 secondes & 1 report/day	50-70-143
		WATER METER SENS'O Direct & reverse flow counting for ARAD Gladiator water meter; Water leakage detection.	A	3,6V / 3600mAh lithium battery Autonomy: 15 years with 1 report/day	50-70-011
		HUMID'O SENSOR Detects the presence of water with a probe or a cable.	A	3.6V - 7200mAh lithium battery Autonomy: >10 years 1 measure/10 mn & 1 report/h	50-70-144
		VAQA'O & VAQA'O+ SENSOR Ambient temperature measurement, hygrometry, VOCs (volatile organic compounds) and CO ₂ . PLUS: atmospheric pressure, lux, presence detection.	A	3,6V / 7500mAh lithium battery 9V-24V / 300mW external power supply Autonomy: >3 years - 1 measure/10 mn & 1 report/h	50-70-168 50-70-074
		HUB'O GATEWAY Dedicated to communications with connected objects with low energy consumption. Hub'O integrates a LoRaWAN 1.0 EU network server and communicates with an external application server or an automation equipment according to the protocols HTTPS - JSON or ModBus RTU / TCP with internal decoding of the data; transmission 3G & Ethernet.	C	230VAC, 50Hz 9V battery for transmitting a power failure alarm	50-70-075



Level of liquid



Active & reactive energy



Air quality



Open/Close detection



Air depression



Meter reading



Pressure



Power



Gateway

FUNCTIONS	VISUAL	DESIGNATION	POWER SUPPLY & AUTONOMY - SF12	REFERENCE
		INDOOR TEMPERATURE SENSOR Measures and transmit over long distance indoor temperature in buildings or houses.	3.6V - 3600mAh lithium battery Autonomy: >10 years - 1 measure/h & 1 report/day; 9 years - 1 measure/h & 1 report/day (data compressed)	50-09-037
		INDOOR THR SENSOR Indoor temperature & relative humidity measurement in buildings or houses.	3,6V - 3600mAh lithium Autonomy: 9 years - 1 measure/h & 1 report/day (data compressed)	50-09-036
		OUTDOOR TEMPERATURE SENSOR Transmits over long distance and in real time accurate temperature measurements; measures UDD (min, max, average).	3.6V - 3600mAh lithium battery Autonomy: >10 years - 1 measure/h & 1 report/day ; 9 years - 1 measure/h & 1 report/day (data compressed)	50-09-039
		REMOTE TEMPERATURE SENSOR Temperature measurement with a remote probe (5 meters) in buildings, temperature-controlled rooms, and cooling towers.	3.6V - 3600mAh lithium battery Autonomy: >10 years - 1 measure/h & 1 report/day (data compressed) ; 9 years - 1 measure/h & 1 report/day (no data compression)	50-09-065
		PULSE S0 SENSOR Transmits data from any pulse meters: water, gas, electricity, energy. Collection: <ul style="list-style-type: none"> Outdoor Pulse S0 Outdoor Pulse S0 AtEx Waterproof Pulse S0 	3.6V - 3600mAh lithium battery Autonomy: 9 years - 1 measure/h & 1 report/day (data compressed)	50-09-038 50-09-041 50-09-063
			FLASH'O SENSOR counts and measures the light pulses of any electronic meter: water, gas, electricity, energy	3.6V - 3600mAh lithium battery Autonomy: >10 years - 1 measure & 1 report/day; 8 years - 1 measure & 1 report/h (data compressed)
		ALARM REPORT SENSOR transforms any dry contact sensor into a remote wireless sensor that monitors industrial equipment status	3.6V - 3600mAh lithium battery Autonomy: >10 years - 1 input state change reporting/day	50-09-046
		VMC GAS VENTILATION SENSOR Measures air depression & temperature in building ventilation chambers with a remote probe.	3.6V - 3600mAh lithium battery Autonomy: >8 years - 1 measure/h & 1 report/day (data compressed)	50-09-080
			SANITARY VENTILATION SENSOR Detects the position On/Off of the equipment by depression measurement.	50-09-034
		SKYDOME SENSOR Verifies that a roof window is properly closed and detects a change of position thanks to an onboard inclinometer.	3.6V - 3600mAh lithium battery Autonomy: > 8 years - 1 measure / 10 secondes & 1 report/day	50-09-078

THEY TRUST US:



For further information, please contact us:

Jean-Luc MALAVAL, Managing Director: +33 (0)6 86 92 55 90

Philippe RONCI, Sales Manager: +33 (0)7 85 02 32 10

Ghada NICOT, Export Manager: +33 (0)2 97 85 67 65

info.watteco@nke.fr



nke WATTECO
6 rue Gutenberg - ZI Kerandré
56700 Hennebont
FRANCE
+33 (0)2 97 36 10 12
www.nke-watteco.com